



ProAir® Evolution

Industrial environments can be dangerous and your SCBA needs to be tough enough for the job. The ProAir® Evolution meets the challenge. Exceeding NIOSH requirements for self-contained breathing apparatus, the ProAir Evolution lets you concentrate on the job at hand, not on your equipment. Draeger assures you the highest quality product available at a price that fits your budget.

Features:

- State of the art pneumatics
- Ergonomic harness and backplate assembly
- Lightweight carbon composite backplate
- Durable nylon harness
- Fail-safe first stage pressure reducer
- Lung Demand Valve delivers 550 lpm
- One size fits all mask
- Panorama Nova mask adaptable to respiratory cartridges
- Panorama Nova and Futura masks have over 90% peripheral vision
- Mask available in EPDM and silicone
- Welding shield available
- Spectacle kits available

Accessories:

- Auxiliary Airline Connection
- Medium Pressure Connection
- Extension Hose & Pouch
- Radio Interface / MegaComin
- Hair Net (NIOSH certified)
- Hard Carrying Case for ProAir and Accessories wall mounting kit also available
- Rapid Adaptor permits use of air purifying filters with the ProAir facemasks.

Draeger offers financing to work within your budget.

Technical Data

Approvals:	NIOSH/MSHA
Operating Temperature	-32° C to 70° C / -25° F to 160° F
Pressure Demand Regulator	
Flow Rate	>550 lpm
Activation	First breath
Bypass	Press or turn to lock
Connection	Positive lock plug-in
Pressure Reducer	
Flow Rate	>1000 lpm
Medium Pressure	90- 130 psi
Dimensions	
Length	approximately 24.5 in.
Width	approximately 12.5 in.
Height	approximately 6 in. (less cylinder)
Warning Whistle	>90 dBA
	Non-aspirating
	Chest Mounted
Warranty	5/15 limited (5 years bumper to bumper) (15 years Pressure reducer)

Weight (approximate)	Unit Weight*	Full Cyl. Weight
Basic unit w/mask	7.5 lbs.	---
4500 psig/60 min. Carbon	25.1 lbs.	17.6 lbs.
4500 psig/45 min. Carbon	21.3 lbs.	13.8 lbs.
4500 psig/30 min. Carbon	18.2 lbs.	10.7 lbs.
4500 psig/45 min. Composite	27.8 lbs.	20.3 lbs.
4500 psig/30 min. Composite	20.2 lbs.	12.7 lbs.
2216 psig/30 min. Composite	20.7 lbs.	13.2 lbs.
2216 psig/30 min. Hoop wrapped	23.6 lbs.	16.1 lbs.
2216 psig/30 min. Aluminum	28.8 lbs.	21.3 lbs.
2216 psig/30 min. Carbon	18.8 lbs.	11.3 lbs.

*Basic unit with mask and cylinder

Draeger Safety Inc.
101 Technology Drive
Pittsburgh, PA 15275-1057
USA
Tel: + 1 412 787-8383
Fax: + 1 412 787-2207
Customer Service:
Tel: 1- 800-922-5518
Fax: 1- 800-922-5519

Draeger Canada Ltd.
7555 Danbro Crescent
Mississauga, Ontario L5N 6P9
Canada
Tel: + 1 905-821-8968
Fax: + 1 905-821-2665

Draeger Service

Draeger Service offers regular inspection and training. We do everything to ensure your equipment will be repaired and back in operation as quickly as possible.

Draeger Expertise

Since 1889, Draeger continues its outstanding reputation in technology for human breathing. Draeger has always been at the forefront in particular hazard protection and the saving of lives in medical and industrial emergencies. Many of the company's 8500 employees are active in research and innovation to ensure that the latest techniques and scientific advances are fully tested before their inclusion in new equipment.



Dräger Worldwide

The Draeger sales and service organization is spread throughout the world. It comprises more than 25 subsidiaries and associated companies to ensure that Draeger is always within easy reach of its clients and in close contact with all important markets. Draeger's ever increasing market share demonstrates the company's international competitiveness and strength.

Draeger has subsidiaries in the following countries: Australia, Austria, Belgium, Bulgaria, Canada, Czech Republic, China, Denmark, France, Great Britain, Hungary, Indonesia, Italy, Japan, Croatia, Netherlands, Norway, Romania, Singapore, South Korea, Slovenia, Slovakia, South Africa, Spain, Sweden, Switzerland, Yugoslavia, USA. Additionally, Draeger is widely represented in Central and South America, Africa, the Middle East, Asia Pacific and Eastern Europe.