

# Talisman Transmitter Systems



ST:1631-2003

### Talissmann Transmitter.

The portable receiver station "Command View", it can be opened like a notebook.



The Talisman transmitter systems for thermal imaging cameras enable you to transmit thermal images directly from the place of operation to a receiver station. This additional information supports you when deciding upon measures during fire-fighting operations.

Two transmitter systems with 2 or 4 channels are available that provide excellent image quality and range. The channel selection function facilitates the use of several cameras at the same time. The transmission unit and antenna are integrated in the Talisman camera housing. Power is supplied via the rechargeable battery of the camera. With certain camera models the transmitter systems are also retrofitable.

Several receiver options are available with or without monitor. You can use commercial monitors for receivers that are not equipped with a monitor.

A special highlight is the "Command View" portable receiver station. Integrated in a sturdy housing it can be opened like a notebook. Command View comes with a big LCD screen, a high-performance rechargeable battery and several external connections. It can be operated without mains supply.

Talisman transmitter systems make the Dräger thermal imaging cameras even more valuable for your operations.

## TECHNICAL DATA TRANSMITTER SYSTEMS

	2-channel	4-channel
Type	analog	analog
Transmitting power	500 mW	500 mW
Frequency	2.45 GHz	2.45 GHz
Channels	2	4
Video standard	PAL	PAL
Range in buildings	50 – 150 m	50-150 m
Range outside buildings	2 km	2 km
Special features:	All information on the display (battery status, etc.) is transmitted	

## TECHNICAL DATA RECEIVER STATIONS

Without Monitor	Stand Alone 2-channel	Stand Alone 4-channel
Power supply	12 V or 240 V	12 V or 240 V
Video output	BNC	BNC
Dimensions	120 x 95 x 35 mm	170 x 90 x 52 mm
Weight	300 g	500 g
Available for	Talisman C plus, Spirit, Elite	Talisman C plus, Spirit

With monitor	Command View 2-channel
Power supply	12 / 24 V or 240 V
Video output	BNC
Operating period (with battery)	2 hours
Display	LCD 200 mm / 8"
Dimensions	212 x 80 x 300 mm
Weight	5-6 kg
Special features:	integrated rechargeable battery + display, can be opened like a notebook
Available for	Talisman C plus, Spirit, Elite

All receivers are supplied with a 10 db high gain antenna and a 3 m antenna cable

subject to changes without notice

## SUBSIDIARIES

### AUSTRALIA

Dräger Safety Pacific Pty. Ltd.  
Notting Hill Vic 3168  
Tel +61 3 92 65 50 00  
Fax +61 3 92 65 50 95

### FRANCE

Draeger Industrie S.A.  
67025 Strasbourg Cedex  
Tel +33 388 40 76 76  
Fax +33 388 40 76 67

### NETHERLANDS

Dräger Safety Nederland B.V.  
2700 AH Zoetermeer  
Tel +31 79 344 46 66  
Fax +31 79 331 62 26

### SPAIN

Draeger Safety Hispania S.A.  
28034 Madrid  
Tel +34 91 358 02 44  
Fax +34 91 729 48 99

### CANADA

Dräger Canada Ltd.  
Mississauga, Ontario L5N 6P9  
Tel +1 905 821 8988  
Fax +1 905 821 2565

### GREAT BRITAIN

Draeger Safety UK Ltd.  
Blyth, Northumberland NE24 4RG  
Tel +44 16 70 35 28 91  
Fax +44 16 70 35 62 66

### SINGAPORE

Draeger Safety Asia Pte. Ltd.  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

### USA

Draeger Safety, Inc.  
Pittsburgh, PA 15275  
Tel +1 412 787 8383  
Fax +1 412 787 2207

### P.R. CHINA

Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

### MEXICO

Draeger Safety S.A. de C.V.  
Querétaro, Oro México  
Tel +1 412 787 8383  
Fax +1 412 787 2207

### REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd.  
Bryanston 2021  
Tel +27 11 465 99 59  
Fax +27 11 465 69 53

### Dräger Safety AG & Co. KGaA

Revalstrasse 1  
23560 Luebeck, Germany  
Tel +49 451 882 0  
Fax +49 451 882 2080  
[www.draeger-safety.com](http://www.draeger-safety.com)