

DATA SHEET



GasAlertClip Extreme

As the world's most popular and widely used zero maintenance gas detector, the GasAlertClip Extreme offers continuous, reliable protection. Available in two year or three year versions, this single gas detector requires no calibration, sensor replacement, battery replacement, or battery charging.

Compatible with the MicroDock II automatic test system, the simplicity of the GasAlertClip Extreme combined with minimal training requirements and negligible maintenance costs, make the GasAlertClip Extreme one of the most cost-effective PPE solutions for facility workers and on-site contractors.

Specifications

Size: 1.1 x 2.0 x 3.2 in. / 2.8 x 5.0 x 8.1 cm

Weight: 2.7 oz. / 76 g

Temperature: **H2S:** -40 to +122°F / -40 to +50°C **CO:** -22 to +122°F / -30 to +50°C **SO2:** -22 to +122°F / -30 to +50°C **O2:** -4 to +122°F / -20 to +50°C

Humidity: 5% - 95% RH (non-condensing)

Alarms: - Visual, vibrating, audible (95dB)- Low, High
Tests: Full function self-test on activation and every 20 hours, and automatic battery test every 2 hours

Typical battery life: Two years (H2S, CO, SO2 or O2) or three years (H2S or CO)

Ratings EMI/RFI: Complies with EMC Directive 89/336/EECIP 66/67

Certifications and approvals: h Class I, Div. 1, Gr. A, B, C, D

American Bureau of Shipping

ATEX: X g II 1 G T4

Ex ia IIC T4

IECEX: Ex ia IIC T4

X: European Conformity

Warranty: 2 or 3 years from activation (given normal operation), plus 1 year shelf life

www.sabreh2s.com